



**Dealer/Customer:** MAXIM TRANSPORTATION (WINNIPEG,MB)TRL  
**Contact:** MAXIM TRANSPORTATION SERVICES INC

**Expiration Date:** 12/24/2024  
**Date:** 10/25/2024

itm	Product	Reference #	Name	Model #	Qty
1	CS1 - Champion 101	C-197128	15x Stock Dry Vans	CS1-1314-21053	15

**Line Item 1**

**Configuration Reference #:** C-197128

**Configuration Name:** 15x Stock Dry Vans

**FG Item:** 26218xxxx

**Product:** CS1 - Champion 101

**Model #:** CS1-1314-21053

**Mode of Transportation:** Customer Pick-Up

**Product**

---

<b>Product</b>	CS1 - Champion 101
<b>Manufacturing Plant</b>	Terre Haute, IN
<b>Model Year</b>	2026

**Geometric Dimensions**

---

<b>CARB/CA Phase 2 GHG</b>	CARB/GHG2 compliance not required.
<b>Packaged Options</b>	None
<b>Serial Identification</b>	Canadian and U.S. Certification
<b>Overall Height</b>	13' 6"
<b>Overall Length</b>	53' 0"
<b>Overall Width</b>	102.36"
<b>Upper Coupler Height</b>	47"
<b>Kingpin Location</b>	36.00"
<b>Landing Gear Location</b>	98.5" From Kingpin
<b>Wedge</b>	1.00" Wedge
<b>Undercarriage Design</b>	Tandem Axle, Slide Air-Ride Suspension, 49" Axle Centers
<b>Miscellaneous Text (TAB A)</b>	None

**Front**



<b>Front Corner Type</b>	4.7" Extruded Aluminum Radius
<b>Front Corner Sheet</b>	0.125" Extruded Aluminum Mill Finish
<b>Front Corner Protectors</b>	None
<b>Front Sheets</b>	Aluminum, 0.050"
<b>Front Upright</b>	Four (4) 16ga STL, 2.5" Hats
<b>Front Vents</b>	None
<b>Quantity and Type of Front Vent</b>	None
<b>Location of Front Vent</b>	None
<b>Electrical Connector and Gladhand Location</b>	Offset Roadside, Overlaid
<b>Hose Couplers (Gladhands)</b>	Great Dane Control and Supply with Urethane Seals
<b>In-Line Air Filter</b>	None
<b>Document Holder</b>	Great Dane Standard with Logo At Roadside Front
<b>Additional Manifest Box</b>	None
<b>Additional Manifest Box Location</b>	None
<b>Miscellaneous Text (TABB)</b>	None
<b>Telematics</b>	
<b>Telematics / Tracking System</b>	FleetPulseGo Track
<b>Alternative Telematics System</b>	...
<b>Telematics System Install and Commission</b>	Factory Furnished and Factory Commissioned
<b>Telematics System Installation Detail</b>	Great Dane Standard Location
<b>Telematics / Tracking Power Supply</b>	
<b>Side Exterior and Structural</b>	
<b>Side Sheet Material</b>	Aluminum, 0.050"
<b>Side Sheet Texture</b>	Flat
<b>Side Post Type</b>	Logistic,0.503" Sgl-Punch "A" (14 Gauge)
<b>Side Post Spacing</b>	16" Centers
<b>Bottom Rail Fasteners</b>	0.38" Aluminum Rivets
<b>Rub Rail Type</b>	None
<b>Rub Rail Location</b>	None
<b>Side Skylight Quantity</b>	None
<b>Side Skylight Location</b>	None
<b>External Protection Package (Lift Pads)</b>	None
<b>Miscellaneous Text (TABC)</b>	None
<b>Rear</b>	
<b>Rear Frame Type</b>	EnduroGuard Swing Door Frame
<b>Header Type</b>	2.5" Narrow Header
<b>Rear Corner Post Lamp Protection</b>	None
<b>Rear Liftgate</b>	None
<b>Rear Bumpers</b>	Rubber Dock Bumper
<b>Rear Impact Guard</b>	Hot Dip Galvanized Steel Rear Impact Guard Bolt on Vertical Weld On Horizontal
<b>Dock Lock Bracing</b>	None



<b>Rear Access System</b>	Handhold Roadside Door (With RIG Intermediate Channel When Clearance Allows)
<b>Tag Bracket Location</b>	Standard Location
<b>License Plate Installation</b>	None
<b>Miscellaneous Text (TABE)</b>	None
<b>Rear Doors</b>	
<b>Rear Door Type</b>	0.50" Composite Swing Door, Dual-Seal Gaskets, Galvanized Steel Cover Sheet
<b>Lockrod</b>	1 Per Door
<b>Hinge per Door</b>	4 Per Rear Door
<b>Rear Door Holdback</b>	S-Link
<b>Rear Door Vent</b>	None
<b>Rear Vent Location</b>	None
<b>Hazardous Placard</b>	None
<b>Haz. Mat. Placard Location</b>	None
<b>Miscellaneous Text (TABF)</b>	None
<b>Roof Options</b>	
<b>Roof Bows</b>	1" Galvanized Steel, 24" Centers
<b>Roof Sheet</b>	Aluminum
<b>Miscellaneous Text (TABG)</b>	None
<b>Floor</b>	
<b>Special Floor Rating</b>	None
<b>Type of Floor</b>	Hardwood, Lam. 1.38"
<b>Hardwood Floor Top Finish</b>	Water Repellant Coating Rear 8'
<b>Hardwood Floor Undercoat</b>	Great Dane Standard (Tectyl Waterbased Primer or Equivalent)
<b>Floor Brand</b>	Factory Choice
<b>Quantity of Wood Floor Screws</b>	3 Screws per Board
<b>Threshold Plate</b>	HDGV Steel Diamondette, 0.125" x 12"
<b>Miscellaneous Text (TABH)</b>	None
<b>Lining / Scuffband</b>	
<b>Side Lining</b>	Thermoplastic Side Lining Recessed Between Uprights
<b>Front Lining</b>	Pine Plywood, 0.50"X48" High, 0.25" to Ceiling
<b>Ceiling Lining</b>	None
<b>Unit Numbers on Lining</b>	None
<b>Rows of Front Scuffband</b>	1 Row
<b>Rows of Side Scuffband</b>	1 Row
<b>Quantity of Rows of Logistic track</b>	None
<b>Miscellaneous Text (TABI)</b>	None
<b>Scuff/Logistic Track</b>	
<b>Type of Front Scuffband</b>	12" Carbon Steel Welded to Coupler, 7 Gauge
<b>Front Scuffband Location</b>	Installed at Floor Level
<b>Front Scuffband Position</b>	Overlaid
<b>Type of Side Scuffband (Row One)</b>	12" Galvanized Steel 18 gauge Roll Formed
<b>Scuffband Location (Row One)</b>	Installed At Floor Level And Overlaid On Lining
<b>Miscellaneous Text (TABJ)</b>	None



### Understructure

---

<b>Upper Coupler Type</b>	3.50" Channel
<b>Bottom Plate Thickness</b>	0.25" with Rolled-Lip
<b>Landing Gear</b>	Jost A451 Magnum, No-Lube, 10yr Vendor Warranty
<b>Landing Gear Foot / Shoe Type</b>	10" X 10" Cushion Foot
<b>Landing Gear Handle Location</b>	Roadside
<b>Landing Gear Lube System</b>	No Special Lube System
<b>Tire Carrier</b>	None
<b>Crossmembers Ahead of Landing Gear</b>	Steel Hat type on 12" Centers, 2" Deep
<b>Crossmembers Over Landing Gear</b>	4" Steel I-Beam on 12" Centers
<b>Bay Area Crossmembers</b>	4" Steel I-Beam on 12" Centers
<b>URG Crossmembers</b>	4" Steel I-Beam on 12" Centers
<b>Extra Crossmembers at Rear</b>	None
<b>Extra URG Rail Length</b>	None
<b>Miscellaneous Text (TBHH)</b>	None

### Aerodynamic Devices

---

<b>Aerodynamic Fairings - Front, Gap Reducers</b>	None
<b>Front Fairing Color</b>	None
<b>Aerodynamic Fairings - Skirts, Undercarriage</b>	Energy Guard Skirt
<b>Side Fairing Color</b>	Default White
<b>Aerodynamic Fairings - Tails, Rear Frame Fairings</b>	None
<b>Rear Fairing Color</b>	None
<b>Miscellaneous Text (TABK)</b>	None

### Suspension

---

<b>Model of Suspension</b>	Hendrickson ULTRA4K 40K
<b>Axle Type</b>	Hendrickson Tapered Spindle Standard Wall
<b>Integrated Wheel End Package</b>	RTR HXL5 Hendrickson Extended-Life 5-Year System
<b>Locking Mechanism</b>	Air-Assist Pin Release
<b>Dump Valve</b>	Surelok Feature
<b>Miscellaneous Text (TABL)</b>	None

### Rear Ramps and Mud Flaps

---

<b>Mudflaps</b>	Great Dane, Black with Logo
<b>Mudflap Quantity/Bracket Material</b>	1-Pair
<b>Mudflap Mounting Location</b>	On Undercarriage
<b>Miscellaneous Text (TABM)</b>	None

### Brakes, Tire Inflation Systems and Wheel Ends

---

<b>Brake Size</b>	16.50" x 7.00"
<b>Brake Actuators</b>	Great Dane Standard 2.5" Stroke
<b>Brake Lining</b>	Standard Brake Lining
<b>Brake Shoe Type</b>	Extended Service
<b>Brake Adjusters</b>	Meritor Automatic 5.50"



<b>Supplemental Brake Stroke Indicator</b>	None
<b>Dust Shield Type</b>	Great Dane Standard
<b>Tire-Inflation-System/Tire/Wheel Options</b>	Hendrickson TIREMAAX PRO
<b>Tire Inflation System Pressure</b>	Great Dane Standard Pressure Setting
<b>Auxiliary Pressure Check Port</b>	None
<b>Wheel Seals</b>	Furnished with Integrated Wheel End System
<b>Axle Spindle Nuts</b>	Furnished with Integrated Wheel End System
<b>Hubcaps</b>	Hubcap To Accommodate Tire Inflation System
<b>Wheel Lubricant</b>	Semi-Fluid Grease Furnished with Integrated Wheel End System
<b>Anti-Lock Brakes</b>	Wabco 2S/1M Easy Stop
<b>ECU Monitored Option</b>	None
<b>Brake Valves</b>	Sealco 110500 Spring Brake Priority
<b>Air-Tank Drain Valve</b>	Manual
<b>Hubodometer YN</b>	None
<b>Miscellaneous Text (TABN)</b>	None
<b>Tires / Wheels / Hubs and Drums</b>	
<b>Rim/Disc Wheel Size</b>	22.5" X 8.25"
<b>Hub/Wheel And Drum</b>	Hendrickson HXL Ductile Iron Hub Piloted 10 Stud Hub With Webb Outboard Cast Drums
<b>Brake Drum Balancing</b>	Supplied Balanced Only
<b>Wheel Type</b>	22.5" Steel Disc Wheel, Hub Piloted, 2HH
<b>Wheel/Rim Vendor</b>	Great Dane
<b>Wheel Stud Options</b>	Long Studs Furnished with HXL Wheel End System
<b>Wheel Spacer (Corrosion Barrier)</b>	None
<b>Tire Size</b>	11R 22.5
<b>Tire Brand</b>	Bridgestone Ecopia R123 (G)
<b>Spare Tire</b>	None
<b>Miscellaneous Text (TABO)</b>	None
<b>Electrical</b>	
<b>Exterior Light Package</b>	All Lights LED, Grote Long Life Light System, AMP Connector, Grote MicroNova Dot Lamps
<b>Electrical Connector Type</b>	Great Dane Standard 7-Way Split Pin
<b>Front Top Rail Lights Loc</b>	1 Top Mounted on Front Corner at 45 Degrees; Roadside and Curbside (Canadian Requirement)
<b>Buckplate Light Type</b>	Grote Series 40, LED Flange Mount
<b>Buckplate Lights Qty &amp; Loc</b>	2 Each Side
<b>Stainless Theft-Resistant Flange for LED Lamps</b>	Installed on Buckplate lamps with Stainless Rivets
<b>Rear Header Light Locations</b>	Center Cluster of 3 with Dual Intensity Brake Indication
<b>Top and Bottom Side Marker Lamps/Location</b>	Standard Lamp Package, 1 Each Side Top Rail @ Front, 1 Each Side Mid-ship Combination (req'd on trlrs 30' and over), 1 Each Side Bottom Rail @ Rear
<b>Midship Turn Signal</b>	Grote LED Combination Turn and Clearance
<b>Location of Turn Signal</b>	Roadside and Curbside, Center of Trailer
<b>Installation of Turn Signal</b>	Install Below Bottom rail



<b>Supplemental Turn Signal</b>	None
<b>Type of Supplemental Turn-Signal</b>	None
<b>Location of Supplemental Turn Signal</b>	None
<b>Installation of Supplemental turn Signal</b>	None
<b>Miscellaneous Text (TABP)</b>	None

**Electrical Interior**

<b>Interior Light Quantity</b>	None
<b>Interior Light Vendor/Type</b>	None
<b>Interior Light Location Width-wise</b>	None
<b>Interior Light Location Length-wise</b>	None
<b>Interior Light Switch Qty / Type / Loc</b>	None
<b>Miscellaneous Text (TABQ)</b>	None

**Finish/Paint/Decal**

<b>Front Finish</b>	Pre-Painted White
<b>Side Finish</b>	Pre-Painted White
<b>Rivet Color</b>	Unpainted
<b>Rear Frame Finish</b>	Great Dane Gray
<b>Rear Door Finish</b>	Pre-Painted White
<b>Undercarriage / Frame Finish</b>	Black Undercoat
<b>Wheel Finish</b>	White Powder Coat
<b>Upper Coupler Finish</b>	Great Dane Standard Coating
<b>Landing Gear Finish</b>	Hot Dip Galvanized Wingplates Fore/Aft Bracing K Brace and Cross Shaft, Leg Finish to Match Undercarriage
<b>Upper Running Gear Finish</b>	Great Dane Standard Coating
<b>Conspicuity Treatment Location</b>	Great Dane on Bottom Rail
<b>Manufacturer's Logo Installation</b>	Red Logos
<b>Installation Of Customer Decals</b>	None
<b>Exterior Unit Numbers</b>	None
<b>Interior Unit Numbers</b>	None
<b>Miscellaneous Text (TABR)</b>	None

**Calculated Values**

<b>Production Line</b>	Dry Production Line 1
<b>Coupler PN</b>	10200271-000001 3.50, 0.25 Btm Plt, 36KP, Painted
<b>CARB Compliance Year</b>	2025

**Insulation**

<b>Floor Insulation</b>	None
-------------------------	------

**Geometric Dimensions**

<b>Drop Depth</b>	None
-------------------	------

**Calculated Values**

<b>Side Door Y/N</b>	No
----------------------	----

**Rear Liftgate**

<b>Liftgate Preparation</b>	None
-----------------------------	------

**Suspension**



**Pintle Hook** None

**Rear Ramps and Mud Flaps**

**Walkramp at Rear** None

---